Revision No.: 01

MATERIAL SAFETY DATA SHEET

1. Identification of the Product and of the Company

Manufacturer Danish Fiber Production ApS

Snedkervej 1 DK 6800 Varde

Tlf.: +45 88 38 98 90 Fax.: +45 75 25 99 53

Trade Name DFP Technical Fibres PP

Chemical Name

Polypropylene:

Propene homopolymer or I-propene, polymer with

ethene.

Type of Product For more detailed information, see technical data sheet.

2. Composition/Information on Ingredients

Main Components Propene homopolymer or I-propene, polymer with

ethene: min. 98%. Chemical formula:

(C3H6) n.

Substances Presenting a Health Hazard None to our knowledge.

Chemical Family Olefin polymer.

Additives Polypropylene antioxidants and stabilizers: 2.0% max.

3. Hazards Identification

Main Hazards None to our knowledge.

Symptoms related to Inhalation If heated to more than 235°C, the product may form

vapours or fumes which may cause irritation of

respiratory tract, resulting in coughing and sensation of

shortness of breath.

Physico-chemical Hazards Combustible if exposed to flames

4. First Aid Measures

Inhalation

Fresh air.

Skin Contact

Treat the affected parts with cold water. If necessary,

consult a skin specialist.

Eye Contact

in case of irritation, wash with copious volumes of water until the irritation disappears (at least 10 minutes). If

necessary, consult eye specialist.

Ingestion

Ingestion during handling is not likely. In case of ingestion of small quantities, no important effect will be observed. In the case of ingestion of larger amounts this

may result in abdominal pain and diarrhoea. If

necessary, consult a doctor.

5. Fire-fighting Measures

Technical Measures

Stop the fire spreading. Call the fire brigade immediately. Evacuate nonessential personnel. Protective clothing, goggles and self-contained breathing equipment should be made available for

firemen.

Extinguishing Media Suitable

For minor fires: carbon dioxide or powder for more extensive fires: foam. Water spray (mist) to cool the

surfaces exposed to the fire.

Not to be used: Do not use water jets (stick jets) in the early stages of extinguishing fire since they could help to

spread the flmes.

Combustion Products

Complete combustion, with an excess of oxygen forms: carbon dioxide and water vapour. Partial combustion also forms carbon monoxide, soot and segregated products: aldehydes, ketones, hydrocarbons and volatile

fatty acids.

6. Accidental Release Measures

Fibres spilled on the floor should be recovered by sweeping or suction, and put in containers to facilitate its disposal.

7. Handling and Storage

Do not store near highly flammable materials. Store away from heating source. Store in dry area to avoid degradation of the boxes and bags.

Storage Temperature

< 100°C, >- 40°C.

Shelf Life

One year.

8. Exposure Controls and Personal Protection

Occupational Exposure Limit

Restorable dust particles not considered to be a hazard.

Peronal Protection

- Respiratory Protection

In case of risk of overexposure to dust, vapour or fumes, it is recommended that a local exhaust system is placed above the conversion equipment, and the working area must be properly ventilated.

9. Physical and Chemical Properties

Appearance

Physical State at 20°C

Colour Odour

Change in Physical State at 1013 hPa

Melting Range (°C):

Flash Point (ASTM D 1929) (°C):

Auto-ignition Temperature (°C):

Explosion Limits (kg/m³)

Lower:

Min. ignition Energy at 20°C (mJ)

Long monofilament or fibrillated fibre strands.

Solid

Translucent or white opaque odourless.

Odourless.

From 160 to 165

± 350

> 380

0.020 (for polymer dust < 63 pm)

Density, mass at 20°C (kg/m³): Solubility in Water (%weight):

Viscosity (mm2/s): Content of Chloride:

Density:

905 (ISOI183) Insoluble. Non-applicable. < 0.001%

 0.905 g/m^3

10. Stability and Reactivity

Stability

Stable under normal operating conditions.

Conditions to avoid

Avoid proximity or contact with flames or sparks. Do not heat to temperatures exceeding 300°C.

11. Toxicological Information

Acute toxicity

Symptoms related to Use:

Inhalation

Low risk for temperatures below 40°C. If heated to more than 235°C the product may form vapours or fumes which may cause irritation of respiratory tract and cause

coughing and sensation of shortness of breath.

Skin Contact

No risk for temperatures below 40°C. Contact with hot

material may cause severe thermal burns.

Eye Contact

Fine dust may cause irritation to ocular mucous, splashing of molten droplets causes ocular tissue injury.

Ingestion

Minimal toxicity.

Carcinogenicity (mg/kg)

IARC (International Agency on Research on Cancer): Category 3: The agent is not classifiable as to its

carcinogenicity to humans.

Mutagenicity

This product has been found to be non-mutagenic as

well as non-genotoxic.

Other

Polyolefines are biologically inert.

12. Ecological Information

Information on Ecological Effects

Avoid losses to the environment whenever possible.

Mobility:

There is a slow loss by evaporation.

Air

Because of its physicochemical properties, the product

generall has low soil mobility.

Soil

Water

Because of its low solubility the product should not be

dangerous for aquatic life.

Persistence and Degradability

Persistent in the environment.

Biodegradation

This substance is slowly biodegradable.

Bioaccumulative Potential

Potential bioaccumulation of the product in environment

is very low

13. Disposal Considerations

Disposal

According to local regulations. Can be disposed of as refuse for reprocessing. Do not dispose of by means of sinks, drains or into the immediate environment. It may be used as fuel in suitably designed installations.

Date of Issue: 2002-01-22

Date of Revision: 2002-02-25

Revision No.: 01

14. Transportation Information

No restriction on transport by road, water, rail, or flight.

15. Regulatory information

Labelling

No labelling is required in accordance with the EEC directives.

16. Other information

The information in this data sheet applies only to the products produced or supplied by us.

It is based on our experience and on the data available to us at the time of its issue and is accurate to the best of our knowledge. The customer is strongly advised to observe and ensure that its employees and customers observe all directions contained herein.

However, no warranty is made or implied that the information is accurate or complete and no liability will be accepted whatsoever arising out of the use of the information or the products designated herein.



WAXMAN FIBRES LTD Port of the Waxman Group

Grove Mills Elland West Yarkthire HX5 9DZ England

Tel: 01422 310600 Fax: 01422 374101 Reg No 2708096 England

Material Safety Data Sheet Kanecaron Type SE

n 1 – Identification	
acturer's Name. Kan	eka Corporation
uters Name: Waxi	man Fibres Ltd
ss: Grov	e Mills Elland West Yorkshire HXS 9DZ
ency Phone Number: 0142	22 310600 England
cal Synonyms: Acry	ylonitriel/ Vinyl Chloride Copolymer
	actylic
n 2: - Hazardous Ingredients	
tous Ingredients: None	
n 3 - Physical Data	
Point: N/A	
Point: N/A	
ic Gravity: 1.25	- 1.30
r Pressure: N/A	
r Density: N/A	이 어느 그는 그는 그를 가는 것이다. 그리 살림, 많은 누워요요요.
lity in water: Insol	luble
ntage, Volatile: <1	
ration Rate: N/A	
rance and Odour. White	e with slight Odour
on 4 - Fire and Explosion Hazard	Data
Point: No □	Data
sive Limit: N/A	
uishing Media: Wate	er and other known extinguishing media
	self-contained breathing apparatus
on 5 Health Hazard Data	
hold Limit Unk	TOM
of Overexposure: Unk	nown
ency and First Aid Procedure: N/A	
on 6 Reactive Data	
ly: Stat	36
dous Polymerisation: Will	not Occur
daus Decomposition Product: SE	fibre does not decompose in normal processing
and the state of t	id contact with strong Oxidizing agent
on 7 - Spill or Leak Procedure	
r Leak procedure: Colli	ect and remove, no special precautions required.
Disposal: Disp	pose of in accordance with local regulations for solid waste erials
Section 8- Special Protection Information	
atony Protection: Not	Necessary
tion: Nat I	Necessary
	Necessary
atory Protection: Not Not Not	Necessary Necessary

The ordinary hazards associated with handling heavy objects and operating various textile machines are encountered in the use of these products. Good industrial practice is recommended throughout the handling and processing of these products, as it is customary and appropriate for the operation being performed. These products contain less than 1% of organic lubricant.